

Valvole a comando pneumatico Pneumatically operated Valves

Dati Tecnici

Pressione d'esercizio: 0÷10 Bar (0÷1,00 MPa)
 Pressione di pilotaggio (5/2): 0,5÷10 Bar (0,05÷1,00 MPa)
 (5/3): 2,1÷10 Bar (0,21÷1,00 MPa)

Peso: 0,161 Kg











Technical data

Working pressure: 0÷10 Bar (0÷1,00 MPa)
 Operating pressure (5/2): 0,5÷10 Bar (0,05÷1,00 MPa)
 (5/3): 2,1÷10 Bar (0,21÷1,00 MPa)

Weight: 0,161 Kg

Codici di ordinazione

Order codes

CODE	REF.
 1272235002	VPR 1/4" 22 5 PN BS OO M
 1272225002	VPR 1/8" 22 5 PN BS OO M
 1272236003	VPR 1/4" 22 5 PN DF OO M
 1272226003	VPR 1/8" 22 5 PN DF OO M
 1272236001	VPR 1/4" 22 6 PN RC CC M
 1272226001	VPR 1/8" 22 6 PN RC CC M
 1272236002	VPR 1/4" 22 6 PN RC CA M
 1272226002	VPR 1/8" 22 6 PN RC CA M
 1272236003	VPR 1/4" 22 6 PN RC CP M
 1272226003	VPR 1/8" 22 6 PN RC CP M

Valvole a doppio comando pneumatico 5/2-5/3 bistabili
 5/2-5/3 Double pneumatic pilot valves

