



Ø mm.	A	B	C	Ch1	Ch2	Ch3	D	D1	E	F	G	H	Ø1	J	K	L1	L2	L3	L4	L5	L6
12 - 16	69	30	30	8	10	24	12	6	8	66	29	10	10	M4	M4	25	18	46	68	123.5	73
20	79	34	37	12	13	27	17	8.5	15	78	32	12	12	M5	M6	25	40	58	108	166	87
25	79	34	37	12	17	27	17	8.5	15	78	32	12	12	M5	M6	25	40	58	108	166	91

Ø mm.	L7	M	N	O	P	Q	R	S	T	T1	U	V	W	X	Y	Z
12 - 16	12	4	4.5	6	8	4.5	5.5	9	5.5	32	24	58	18	18	22	49.5
20	10	5	5.5	9	10	7.5	6.5	11	6.5	38	38	68	32.5	20	23	58
25	10	6	5.5	9	10	7.5	6.5	11	6.5	38	38	68	32.5	20	23	58

MLCHB

UNITA' DI GUIDA AD "H" CON BUSSOLE IN BRONZO

GUIDE UNIT "H" WITH SELF LUBRICATING SINTERED BRONZE

ISO6432

CORSE STANDARD mm. - STD STROKES

Ø mm.	50	100	160	200	250
12 - 16	X	X	X	X	X
20	X	X	X	X	X
25	X	X	X	X	X